

**HAZWOPER PART II:
HAZARD IDENTIFICATION AND
CONTROL**

T290

Name: _____

Date: _____

Test Questions:

1. The OSHA Hazwoper Standard applies to:
 - A. Employees who are exposed or potentially exposed to hazardous substances during clean-up operations or emergency response.
 - B. All employees who work in the United States
 - C. All employees who work in chemical plants
 - D. All employees who work in manufacturing

2. The Hazwoper Standard requires employers to conduct a preliminary evaluation of a site's characteristics prior to entry to:
 - A. Determine the scope of the operation
 - B. Identify potential site hazards
 - C. Aid in the selection of appropriate employee protection methods
 - D. Both B and C

3. Which of the following may be used to reduce and maintain employee exposure to or below the permissible exposure limits for hazardous substances?
 - A. Engineering controls
 - B. Safe work practices
 - C. Use of personal protective equipment
 - D. All of the above

4. The OSHA Hazwoper Standard requires air monitoring when:
 - A. Outside temperatures may exceed 100 degrees
 - B. Rescue teams are not available
 - C. Employees may risk exposure to hazardous concentrations of hazardous substances
 - D. All of the above

5. Decontamination procedures are designed to:
 - A. Eliminate odors from clothing and equipment used in hazardous waste operations
 - B. Minimize employee contact with hazardous substances or with equipment that has contacted hazardous substances
 - C. Ensure that clothing and equipment used in hazardous waste operations stays in good condition
 - D. Ensure that clothing and equipment used in hazardous waste operations stays on site and is available for later use.

Signature