

**CITY OF FRESNO
PUBLIC WORKS DEPARTMENT
PLANTING SPACING REQUIREMENTS**

Refer to Section 26.2.1 (C) of the City of Fresno Standard Specifications

The landscape designer and contractor are to ensure that the spacing of the trees conforms to the following minimum spacing guidelines. Trees shall be planted:

1. 30 ft. from street corners and signs
2. 15 ft. from alleys
3. 10 ft. from drive approaches
4. 20 ft. from street light poles
5. 15 ft. from power poles
6. 10 ft. from fire hydrants
7. 6 ft. from concrete improvements, unless otherwise shown on plans
8. 8 ft. from sewer lines
9. 3 ft. from gas and electrical lines
10. 3 ft. from water lines
11. 3 ft. from telephone and cable television lines
12. 20 ft. from other acceptable trees
13. 3 ft. from adjoining property lines
14. 5 ft. from underground utility boxes
15. 5 ft. from overhangs
16. 5 ft. from street signage (pedestrian crossing, merging traffic, No Parking)
17. 30 ft. from front of signal light poles

Additional Requirements

1. No trees to be planted under power pole guy wires; can be planted five feet from guy wire ground support
2. No large trees to be planted under hot wires
3. No trees to be planted in tree wells or park strips in front of doorways
4. No trees to be planted over roof drains
5. No large trees to be planted over sewer mainlines